



| | | | | |
|--------------------------------------|-----|-------------|----------------|-------|
| 减速比 (Ratio i) | 9 | 12/16/20/32 | 15/40/25/50/30 | 64/80 |
| 额定承载扭矩 (Rated load torque) Nm | 40 | 110 | 90 | 50 |
| 最大加速力矩 (Max. acceleration torque) Nm | 72 | 198 | 162 | 90 |
| 急停扭矩 (Emergency stop torque) Nm | 120 | 330 | 270 | 150 |

| | | | |
|------------------------------|-----------|--------------------------------|------------------------------|
| 精密行星减速机技术参数 | | | |
| 容许最大径向载荷 (Max. radial load) | 900N | 空载力矩20℃ (No-load torque) | ≤ 0.2Nm |
| 容许最大轴向载荷 (Max. axial load) | 1200N | 润滑 (Lubrication) | 合成润滑油 (Synthetic grease) |
| 额定输入转速 (Nominal input speed) | 3000r/min | 使用环境温度 (Operation temperature) | -15℃~+90℃ |
| 最大输入转速 (Max input speed) | 6000r/min | 使用寿命 (Service life) | ≥20000h |
| 噪音 (Noise) | ≤ 60db | 防护等级 (Protection grade) | IP54 |
| 回程间隙 (Backlash) | 12arcmin | PL系列 | Tel/电话: 0533-6288333 6288444 |
| | | P2 L2 | Fax/传真: 0533-6288411 |
| | | | Web/网址: www.newstart.cn |

| | |
|---|------|
| 未注线性尺寸极限偏差 Unmarked tolerance | |
| 0.5-3 | ±0.2 |
| 3-6 | ±0.3 |
| 6-30 | ±0.5 |
| 30-120 | ±0.8 |
| 120-400 | ±1.2 |
| 400-1000 | ±2 |
| 精密行星减速机 Precision Planetary Gear Boxes | |
|  | |
| PF080L2-i-P2-S2 19-40-70-90-M6 | |
| A. PF. | 080. |