


減速比 (Ratio i)	60/64/80/160/256	100/120/200/320	512
額定承載扭矩 (Rated load torque) Nm	110	90	50
最大加速力矩 (Max.acceleration torque) Nm	198	162	90
急停扭矩 (Emergency stop toque) Nm	330	270	150

未注线性尺寸极限偏差 Unmarked tolerance	
0.5-3	±0.2
3-6	±0.3
6-30	±0.5
30-120	±0.8
120-400	±1.2
400-1000	±2

精密行星减速机技术参数					精密行星减速机 Precision Planetary Gear Boxes	
容许最大径向载荷 (Max.radial load)	900N	空载力矩20℃(No-load torque)		≤ 0.2Nm		
容许最大轴向载荷 (Max.axial load)	1200N	润滑(Lubrication)		合成润滑油 (Synthetic grease)		
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)		-15℃~+90℃		
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)		≥20000h		
噪音 (Noise)	≤ 65db	防护等级 (Protection grade)		IP54		
回程间隙 (Backlash)	18arcmin	PL系列		Tel/电话: 0533-6288333 6288444		
		P2 L3		Fax/传真: 0533-6288411		
				Web/网址: www.newstart.cn		
				 纽氏达特		
				WPF080L3-i-P2-S2 19-40-80-100-M6		
				A. WPF. 080.		