


减速比 (Ratio i)		60/64/80/160/256		100/120/200/320	512	6-30	±0.5
额定承载扭矩 (Rated load torque)		Nm	260	230	120	30-120	±0.8
最大加速力矩 (Max.acceleration torque)		Nm	468	414	216	120-400	±1.2
急停扭矩 (Emergency stop torque)		Nm	780	690	360	400-1000	±2
精密行星减速机技术参数						精密行星减速机	
容许最大径向载荷 (Max.radial load)		900N	空载力矩20℃ (No-load torque)		≤ 0.36Nm	Precision Planetary Gear Boxes	
容许最大轴向载荷 (Max.axial load)		1200N	润滑 (Lubrication)		合成润滑脂 (Synthetic grease)		
额定输入转速 (Nominal input speed)		3000r/min	使用环境温度 (Operation temperature)		-15℃~+90℃	纽氏達特	
最大输入转速 (Max input speed)		6000r/min	使用寿命 (Service life)		≥20000h	WPL120L3-i-P2-S2	
噪音 (Noise)		≤ 68db	防护等级 (Protection grade)		IP54	22-58-110-145-M8	
回程间隙 (Backlash)		18arcmin	WPL系列		Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn	A. WPL. 120.	
			P2 L3				