


减速比 (Ratio i)	9	12/16/20/32	15/40/25/50/30	64/80				6-30	±0.5
额定承载扭矩 (Rated load torque) Nm	125	260	230	120				30-120	±0.8
最大加速力矩 (Max.acceleration torque) Nm	225	468	414	216				120-400	±1.2
急停扭矩 (Emergency stop torque) Nm	375	780	690	360				400-1000	±2

精密行星减速机技术参数					精密行星减速机 Precision Planetary Gear Boxes
容许最大径向载荷 (Max. radial load)	1850N	空载力矩20℃ (No-load torque)		≤ 0.36Nm	 NEWSTART® 紐氏達特
容许最大轴向载荷 (Max. axial load)	2800N	润滑 (Lubrication)		合成润滑脂 (Synthetic grease)	
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (operation temperature)		-15℃ ~ +90℃	
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)		≥ 20000h	
噪音 (Noise)	≤ 63db	防护等级 (Protection grade)		IP54	
回程间隙 (Backlash)	12arcmin	PL 系列		Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn	PL 120L2-i-P2-S2 19-40-70-90-M6
		P2 L2			A. PL. 120.