

1 2 3 4 5 6


A

B


C

D

输出端 Input



输入端 Output



A

B

C

D

减速比 (Ratio i)	9	12/16/20/32	15/40/25/50/30	64/80					未注线性尺寸极限偏差 Unmarked tolerance
额定承载扭矩 (Rated load torque) Nm	125	260	230	120					0.5-3 ±0.2
最大加速力矩 (Max. acceleration torque) Nm	225	468	414	216					3-6 ±0.3
急停扭矩 (Emergency stop torque) Nm	375	780	690	360					6-30 ±0.5
									30-120 ±0.8
									120-400 ±1.2
									400-1000 ±2

精密行星减速机技术参数

容许最大径向载荷 (Max. radial load)	1850N	空载力矩20℃ (No-load torque)	≤ 0.36Nm	 PL120L2-i-P2-S2 19-40-70-90-M6 A. PL. 120.
容许最大轴向载荷 (Max. axial load)	2800N	润滑 (Lubrication)	合成润滑脂 (Synthetic grease)	
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)	-15℃~+90℃	
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)	≥20000h	
噪音 (Noise)	≤ 63db	防护等级 (Protection grade)	IP54	
回程间隙 (Backlash)	12arcmin	PL系列	Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn	
		P2 L2		

1 2 3 4 5 6