


减速比 (Ratio i)		9	12/16/20/32	15/40/25/50/30	64/80			6-30	±0.5
额定承载扭矩(Rated load torque)		Nm	125	260	230	120		30-120	±0.8
最大加速力矩 (Max.acceleration torque)		Nm	225	468	414	216		120-400	±1.2
急停扭矩 (Emergency stop toque)		Nm	375	780	690	360		400-1000	±2
精密行星减速机技术参数								精密行星减速机	
容许最大径向载荷 (Max.radial load)		1850N	空载力矩20℃(No-load torque)			≤ 0.36Nm		Precision Planetary Gear Boxes	
容许最大轴向载荷 (Max.axial load)		2800N	润滑(Lubrication)			合成润滑脂 (Synthetic grease)		 紐氏達特	
额定输入转速 (Nominal input speed)		3000r/min	使用环境温度(Operation temperature)			-15℃~+90℃		PL120L2-i-P2-S2 22-58-110-145-M8	
最大输入转速 (Max input speed)		6000r/min	使用寿命(Service life)			≥20000h			
噪音 (Noise)		≤ 63db	防护等级(Protection grade)			IP54		A. PL. 120.	
回程间隙 (Backlash)		12arcmin				PL系列			
						P2 L2		Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn	