



减速比 (Ratio i)		3	4	5	6	8	10	
额定承载扭矩 (Rated load torque)	Nm	125	260	230	128	120	70	
最大加速力矩 (Max. acceleration torque)	Nm	225	468	414	6	216	126	
急停扭矩 (Emergency stop torque)	Nm	375	780	690	6	360	210	

未注线性尺寸极限偏差 Unmarked tolerance	
0.5-3	±0.2
3-6	±0.3
6-30	±0.5
30-120	±0.8
120-400	±1.2
400-1000	±2

精密行星减速机技术参数					精密行星减速机	
容许最大径向载荷 (Max. radial load)	1850N	空载力矩20℃ (No-load torque)		≤ 0.36Nm		
容许最大轴向载荷 (Max. axial load)	2800N	润滑 (Lubrication)		合成润滑脂 (Synthetic grease)		
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)		-15℃~+90℃		
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)		≥20000h		
噪音 (Noise)	≤ 63db	防护等级 (Protection grade)		IP54		
回程间隙 (Backlash)	10arcmin	PL 系列		Tel/电话: 0533-6288333 6288444		
		P2 L1		Fax/传真: 0533-6288411		
				Web/网址: www.newstart.cn		
				A. PL. 120.		