

123456



A

B


C

D

输出端 Output



输入端 Input



								未注线性尺寸极限偏差 Unmarked tolerance	
								0.5-3	±0.2
								3-6	±0.3
								6-30	±0.5
								30-120	±0.8
								120-400	±1.2
								400-1000	±2
精密行星减速机技术参数									
减速比 (Ratio i)	9	12/16/20/32	15/40/25/50/30	64/80				精密行星减速机	
额定承载扭矩 (Rated load torque) Nm	400	800	700	450				Precision Planetary Gear Boxes	
最大加速力矩 (Max. acceleration torque) Nm	720	1440	1260	810				NEWSTART 纽氏达特	
急停扭矩 (Emergency stop torque) Nm	1200	2400	2100	1350				PL160L2-i-P2-S2	
容许最大径向载荷 (Max. radial load)								22-58-110-145-M8	
容许最大轴向载荷 (Max. axial load)								A. PL. 160.	
额定输入转速 (Nominal input speed)									
最大输入转速 (Max input speed)									
噪音 (Noise)									
回程间隙 (Backlash)									
空载力矩20℃ (No-load torque)									
润滑 (Lubrication)									
使用环境温度 (Operation temperature)									
使用寿命 (Service life)									
防护等级 (Protection grade)									
PL系列									
P2 L2									
Tel/电话: 0533-6288333 6288444									
Fax/传真: 0533-6288411									
Web/网址: www.newstart.cn									

123456

A

B

C

D