


减速比 (Ratio i)		3	4	5	6	8	10	
额定承载扭矩 (Rated load torque)	Nm	400	800	700	550	450	210	
最大加速力矩 (Max. acceleration torque)	Nm	720	1440	1260	990	810	378	
急停扭矩 (Emergency stop torque)	Nm	1200	2400	2100	1650	1350	630	

精密行星减速机技术参数				精密行星减速机			
容许最大径向载荷 (Max. radial load)	3600N	空载力矩 20℃ (No-load torque)	$\leq 0.72Nm$	 紐氏達特			
容许最大轴向载荷 (Max. axial load)	8000N	润滑 (Lubrication)	合成润滑脂 (Synthetic grease)				
额定输入转速 (Nominal input speed)	2000r/min	使用环境温度 (Operation temperature)	-15℃~+90℃	WPL0160L1-i-P2-S2 35-79-114.3-200-M12			
最大输入转速 (Max input speed)	4000r/min	使用寿命 (Service life)	$\geq 20000h$				
噪音 (Noise)	$\leq 70db$	防护等级 (Protection grade)	IP54	A. WPL. 160.			
回程间隙 (Backlash)	14arcmin						

未注线性尺寸极限偏差 Unmarked tolerance	
0.5-3	± 0.2
3-6	± 0.3
6-30	± 0.5
30-120	± 0.8
120-400	± 1.2
400-1000	± 2

Tel/ 电话: 0533-6288333 6288444
Fax/ 传真: 0533-6288411
Web/ 网址: www.newstart.cn