

1

2

3

4

5

6

A

B

C

D

A

B

C

D

减速比 (Ratio i)		60/64/80/160/256	100/120/200/320	512	6-30	±0.5
额定承载扭矩(Rated load torque)		Nm 800	700	450	30-120	±0.8
最大加速力矩 (Max.acceleration torque)		Nm 1440	1260	810	120-400	±1.2
急停扭矩 (Emergency stop torque)		Nm 2400	2100	1350	400-1000	±2
精密行星减速机技术参数					精密行星减速机	
容许最大径向载荷 (Max. radial load)		3600N	空载力矩20℃ (No-load torque)		≤ 0.72Nm	
容许最大轴向载荷 (Max. axial load)		8000N	润滑 (Lubrication)		合成润滑脂 (Synthetic grease)	
额定输入转速 (Nominal input speed)		2000r/min	使用环境温度 (Operation temperature)		-15℃~+90℃	
最大输入转速 (Max input speed)		4000r/min	使用寿命 (Service life)		≥20000h	
噪音 (Noise)		≤ 70db	防护等级 (Protection grade)		IP54	
回程间隙 (Backlash)		18arcmin	WPL系列		Tel/电话: 0533-6288333 6288444	
			P2 L3		Fax/传真: 0533-6288411	
					Web/网址: www.newstart.cn	
					A. WPL.	160.