

1

2

3

4

5

6

A

B

C


D

A

B

C

D

减速比 (Ratio i)		9	12/16/20/32	15/40/25/50/30	64/80			6-30	±0.5
额定承载扭矩 (Rated load torque)		Nm 400	800	700	450			30-120	±0.8
最大加速力矩 (Max. acceleration torque)		Nm 720	1440	1260	810			120-400	±1.2
急停扭矩 (Emergency stop torque)		Nm 1200	2400	2100	1350			400-1000	±2
精密行星减速机技术参数									精密行星减速机
容许最大径向载荷 (Max. radial load)		3600N	空载力矩20℃ (No-load torque)			≤ 0.72Nm			Precision Planetary Gear Boxes
容许最大轴向载荷 (Max. axial load)		8000N	润滑 (Lubrication)			合成润滑脂 (Synthetic grease)			 NEWSTART 紐氏達特
额定输入转速 (Nominal input speed)		2000r/min	使用环境温度 (Operation temperature)			-15℃~+90℃			
最大输入转速 (Max input speed)		4000r/min	使用寿命 (Service life)			≥20000h			WPL160L2-i-P2-S2 38-80-180-215-M12
噪音 (Noise)		≤ 70db	防护等级 (Protection grade)			IP54			
回程间隙 (Backlash)		14arcmin			WPL系列		Tel/电话: 0533-6288333 6288444		A. WPL. 160.
					P1 L2		Fax/传真: 0533-6288411		
							Web/网址: www.newstart.cn		

1

2

3

4

5

6