


减速比 (Ratio i)		3	4	5	6	8		3-6	±0.3
额定承载扭矩(Rated load torque)		Nm	10	20	18	6	5	6-30	±0.5
最大加速力矩 (Max.acceleration torque)		Nm	18	36	32.4	10.8	9	30-120	±0.8
急停扭矩 (Emergency stop toque)		Nm	30	60	54	18	15	120-400	±1.2
								400-1000	±2
精密行星减速机技术参数								精密行星减速机	
容许最大径向载荷 (Max.radial load)		220N	空载力矩20℃(No-load torque)			≤ 0.36Nm			 PL40L1-i-P2-S2-8-25-30-46-M4
容许最大轴向载荷 (Max.axial load)		200N	润滑(Lubrication)			合成润滑脂 (Synthetic grease)			
额定输入转速 (Nominal input speed)		3000r/min	使用环境温度(Operation temperature)			-15℃~+90℃			A. PL. 040.
最大输入转速 (Max input speed)		6000r/min	使用寿命(Service life)			≥20000h			
噪音 (Noise)		≤ 58db	防护等级(Protection grade)			IP54			
回程间隙 (Backlash)		16arcmin	PL系列			Tel/电话: 0533-6288333 6288444 Fax /传真: 0533-6288411 Web/网址: www.newstart.cn			
			P2 L1						

未注线性尺寸极限偏差 Unmarked tolerance	
0.5-3	±0.2
3-6	±0.3
6-30	±0.5
30-120	±0.8
120-400	±1.2
400-1000	±2