

1

2

3

4

5

6

A

B

C


D

A

B

C

D

未注线性尺寸极限偏差 Unmarked tolerance				0.5-3	±0.2
				3-6	±0.3
				6-30	±0.5
				30-120	±0.8
				120-400	±1.2
				400-1000	±2
精密行星减速机技术参数					
精密行星减速机					
Precision Planetary Gear Boxes					
					
WPL060L3-i-P2-S2					
8-24-38.1-1147.14-M4					
A. WPL. 060.					
Tel/电话: 0533-6288333 6288444					
Fax/传真: 0533-6288411					
Web/网址: www.newstart.cn					
P2 L3					
WPL系列					
防护等级(Protection grade)					
IP54					
使用寿命(Service life)					
≥20000h					
使用环境温度(Operation temperature)					
-15℃~+90℃					
合成润滑脂 (Synthetic grease)					
润滑 (Lubrication)					
空载力矩20℃ (No-load torque)					
≤ 0.1Nm					
容许最大轴向载荷 (Max.axial load)					
600N					
容许最大径向载荷 (Max.radial load)					
480N					
回程间隙 (Backlash)					
18arcmin					
噪音 (Noise)					
≤ 63db					
最大输入转速 (Max input speed)					
6000r/min					
额定输入转速 (Nominal input speed)					
3000r/min					
最大加速力矩 (Max.acceleration torque) Nm					
81					
额定承载扭矩 (Rated load torque) Nm					
45					
减速比 (Ratio i)					
60/64/80/160/256					
100/120/200/320					
512					
急停扭矩 (Emergency stop toque) Nm					
135					
123					
54					