



减速比 (Ratio i)		3	4	5	6	8	10	
额定承载扭矩 (Rated load torque)	Nm	22	45	41	26	18	15	
最大加速力矩 (Max. acceleration torque)	Nm	39.6	81	73.8	46.8	32.4	27	
急停扭矩 (Emergency stop torque)	Nm	66	135	123	78	54	45	

精密行星减速机技术参数				精密行星减速机			
容许最大径向载荷 (Max. radial load)	480N	空载力矩 20℃ (No-load torque)	≤ 0.1Nm	精密行星减速机			
容许最大轴向载荷 (Max. axial load)	600N	润滑 (Lubrication)	合成润滑脂 (Synthetic grease)	Precision Planetary Gear Boxes			
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)	-15℃~+90℃	NEWSTART 纽氏達特			
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)	≥ 20000h	WPL060L1-i-P2-S2			
噪音 (Noise)	≤ 63db	防护等级 (Protection grade)	IP54	14-30-50-70-M5			
回程间隙 (Backlash)	14arcmin	WPL系列		A. WPL. 060.			
		P2 L1					
				Tel/ 电话: 0533-6288333 6288444			
				Fax/ 传真: 0533-6288411			
				Web/ 网址: www.newstart.cn			

未注线性尺寸极限偏差	
Unmarked tolerance	
0.5-3	±0.2
3-6	±0.3
6-30	±0.5
30-120	±0.8
120-400	±1.2
400-1000	±2