


減速比 (Ratio i)		3	4	5	6	8	10	
額定承載扭矩(Rated load torque)	Nm	22	45	41	26	18	15	
最大加速力矩 (Max.acceleration torque)	Nm	39. 6	81	73. 8	46. 8	32. 4	27	
急停扭矩 (Emergency stop toque)	Nm	66	135	123	78	54	45	

未注线性尺寸极限偏差 Unmarked tolerance	
0.5-3	±0.2
3-6	±0.3
6-30	±0.5
30-120	±0.8
120-400	±1.2
400-1000	±2

精密行星减速机技术参数

容许最大径向载荷 (Max. radial load)	480N	空载力矩20℃ (No-load torque)	≤ 0.1Nm
容许最大轴向载荷 (Max. axial load)	600N	润滑 (Lubrication)	合成润滑脂 (Synthetic grease)
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (operation temperature)	-15℃ +90℃
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)	≥20000h
噪音 (Noise) ≤	60db	防护等级 (Protection grade)	IP54
回程间隙 (Backlash)	10arcmin	PL系列	Tel/电话: 0533-6288333 6288444
		P2 L1	Fax/传真: 0533-6288411 Web/网址: www.dewstart.cn

	精密行星减速机 Precision Planetary Gear Boxes  NEWSTART 紐氏達特
	PL60L1-i-P2-S2- 14-30-50-70-M5
A. PL.	060.