


精密行星减速机技术参数				未注线性尺寸极限偏差 Unmarked tolerance	
减速比 (Ratio i)	60/64/80/160/256	100/120/200/320	512	0.5-3	±0.2
额定承载扭矩 (Rated load torque)	Nm 45	41	18	3-6	±0.3
最大加速力矩 (Max. acceleration torque)	Nm 81	73.8	32.4	6-30	±0.5
急停扭矩 (Emergency stop torque)	Nm 135	123	54	30-120	±0.8
				120-400	±1.2
				400-1000	±2
精密行星减速机技术参数				精密行星减速机 Precision Planetary Gear Boxes	
容许最大径向载荷 (Max. radial load)	480N	空载力矩20℃ (No-load torque)	≤ 0.1Nm	 PL060L3-i-P2-S2 14-30-50-70-M5	
容许最大轴向载荷 (Max. axial load)	600N	润滑 (Lubrication)	合成润滑脂 (Synthetic grease)		
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)	-15℃~+90℃	A. PL. 060.	
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)	≥20000h		
噪音 (Noise)	≤ 60db	防护等级 (Protection grade)	IP54	Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn	
回程间隙 (Backlash)	14arcmin	PL系列 P2 L3			