


減速比 (Ratio i)	9	12/16/20/32	15/40/25/50/30	64/80			
額定承载扭矩(Rated load torque) Nm	40	110	90	50			
最大加速力矩 (Max.acceleration torque) Nm	72	198	162	90			
急停扭矩 (Emergency stop torque) Nm	120	330	270	150			

未注线性尺寸极限偏差 Unmarked tolerance

0.5-3	± 0.2
3-6	± 0.3
6-30	± 0.5
30-120	± 0.8
120-400	± 1.2
400-1000	± 2

精密行星减速机技术参数			
容许最大径向载荷 (Max.radial load)	900N	空载力矩20℃(No-load torque)	≤ 0.2Nm
容许最大轴向载荷 (Max.axial load)	1200N	润滑 (Lubrication)	合成润滑油 (Synthetic grease)
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)	-15℃~+90℃
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)	≥20000h
噪音 (Noise)	≤ 65db	防护等级 (Protection grade)	IP54
回程间隙 (Backlash)	14arcmin	WPL系列	Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411
		P1 L2	Web/网址: www.newstar.cn

精密行星减速机	
Precision Planetary Gear Boxes	
	
WPL080L2-i-P2-S2 19-40-70-90-M5	
A. WPL.	080.