


減速比 (Ratio i)	9	12/16/20/32	15/40/25/50/30	64/80			
額定承載扭矩 (Rated load torque) Nm	40	110	90	50			
最大加速力矩 (Max. acceleration torque) Nm	72	198	162	90			
急停扭矩 (Emergency stop torque) Nm	120	330	270	150			

未注线性尺寸极限偏差  
Unmarked tolerance

0.5-3	$\pm 0.2$
3-6	$\pm 0.3$
6-30	$\pm 0.5$
30-120	$\pm 0.8$
120-400	$\pm 1.2$
400-1000	$\pm 2$

容许最大径向载荷 (Max.radial load)	900N	空载力矩20℃(No-load torque)	≤ 0.2Nm
容许最大轴向载荷 (Max.axial load)	1200N	润滑(Lubrication)	合成润滑油 (Synthetic grease)
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度(operation temperature)	-15℃~+90℃
最大输入转速 (Max input speed)	6000r/min	使用寿命(Service life)	≥20000h
噪音 (Noise)	≤ 65db	防护等级(Protection grade)	IP54
回程间隙 (Backlash)	14arcmin	WPL 系列	Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn
		PI L2	

	精密行星减速机 Precision Planetary Gear Boxes
)	 紐仕達特
	WPL080L2-i-P2-S2 14-30-50-70-M5
	A. WPL. 080.