




A

B

C


D



減速比 (Ratio i)	60/64/80/160/256	100/120/200/320	512
額定承載扭矩 (Rated load torque) Nm	110	90	50
最大加速力矩 (Max. acceleration torque) Nm	198	162	90
急停扭矩 (Emergency stop torque) Nm	330	270	150

未注线性尺寸极限偏差 Unmarked tolerance	
0.5-3	± 0.2
3-6	± 0.3
6-30	± 0.5
30-120	± 0.8
120-400	± 1.2
400-1000	± 2

容许最大径向载荷 (Max. radial load)	900N	空载力矩20℃(No-load torque)	≤ 0.2Nm
容许最大轴向载荷 (Max. axial load)	1200N	润滑(Lubrication)	合成润滑油 (Synthetic grease)
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度(Operation temperature)	-15℃~+90℃
最大输入转速 (Max input speed)	6000r/min	使用寿命(Service life)	≥20000h
噪音 (Noise) ≤	60db	防护等级(Protection grade)	IP54
回程间隙 (Backlash)	14arcmin	PL系列	Tel/电话: 0533-6288333 6288444
		P2 L3	Fax/传真: 0533-6288411
			Web/网址: www.nmccn.cn

精密行星減速機 Precision Planetary Gear Boxes	
 NEWSTART® 紐氏達特	
PL060L3-i-P2-S2 19-40-70-90-M6	
A. PL.	080.