



减速比 (Ratio i)		9	12/16/20/32	15/40/25/50/30	64/80			6-30	±0.5
额定承载扭矩(Rated load torque)		Nm	40	110	90	50		30-120	±0.8
最大加速力矩 (Max.acceleration torque)		Nm	72	198	162	90		120-400	±1.2
急停扭矩 (Emergency stop toque)		Nm	120	330	270	150		400-1000	±2
精密行星减速机技术参数								精密行星减速机	
容许最大径向载荷 (Max.radial load)		900N	空载力矩20℃ (No-load torque)			≤ 0.2Nm		Precision Planetary Gear Boxes	
容许最大轴向载荷 (Max.axial load)		1200N	润滑 (Lubrication)			合成润滑脂 (Synthetic grease)		 紐氏達特	
额定输入转速 (Nominal input speed)		3000r/min	使用环境温度 (Operation temperature)			-15℃~+90℃		PL080L2-i-P2-S2	
最大输入转速 (Max input speed)		6000r/min	使用寿命 (Service life)			≥20000h		14-30-50-70-M5	
噪音 (Noise)		≤ 60db	防护等级 (Protection grade)			IP54		A. PL. 080.	
回程间隙 (Backlash)		12arcmin			PL系列				
		P2 L2							
								Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn	