

1

2

3

4

5

6


A

B



C

D

输出端
OutPut



输入端
InPut




A

B

C

D

减速比 (Ratio i)		3	4	5	6	8	10		3-6	±0.3
额定承载扭矩 (Rated load torque) Nm		125	260	230	128	120	70		6-30	±0.5
最大加速力矩 (Max.acceleration torque) Nm		225	468	414	230.4	216	126		30-120	±0.8
急停扭矩 (Emergency stop toque) Nm		375	780	690	384	360	210		120-400	±1.2
									400-1000	±2
精密行星减速机技术参数									精密行星减速机	
									Precision Planetary Gear Boxes	
容许最大径向载荷 (Max.radial load)	1850N	空载力矩20℃(No-load torque)				≤ 0.36Nm				PS115L1-i-P2-S2 19-40-70-90-M6
容许最大轴向载荷 (Max.axial load)	2800N	润滑(Lubrication)				合成润滑油 (Synthetic grease)				
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度(Operation temperature)				-15℃~+90℃				
最大输入转速 (Max input speed)	6000r/min	使用寿命(Service life)				≥20000h				
噪音 (Noise)	≤ 63db	防护等级(Protection grade)				IP54				
回程间隙 (Backlash)	8arcmin				PS系列		Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn		A. PS.	115.
					P2 L1					

1

2

3

4

5

6