

A

B

C

D

1

2



3

4


5

6

输出端  
OutPut



输入端  
InPut



A

B

C

D

精密行星减速机技术参数				精密行星减速机	
减速比 (Ratio i)	60/64/80/160/256	100/120/200/320	512	精密行星减速机	
额定承载扭矩 (Rated load torque)	Nm	260	230	Precision Planetary	
最大加速力矩 (Max. acceleration torque)	Nm	468	414	Gear Boxes	
急停扭矩 (Emergency stop torque)	Nm	780	690	NEWSTART	
				纽氏達特	
容许最大径向载荷 (Max. radial load)	1850N	空载力矩20℃ (No-load torque)	≤ 0.36Nm	PS115L3-i-P2-S2	
容许最大轴向载荷 (Max. axial load)	2800N	润滑 (Lubrication)	合成润滑油 (Synthetic grease)	24-58-110-145-M8	
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)	-15℃~+90℃	A. PS. 115.	
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)	≥20000h		
噪音 (Noise)	≤ 63db	防护等级 (Protection grade)	IP54		
回程间隙 (Backlash)	12arcmin	PS系列	Tel/电话: 0533-6288333 6288444		
		P2 L3	Fax/传真: 0533-6288411		
			Web/网址: www.newstart.cn		

未注线性尺寸极限偏差 Unmarked tolerance	
0.5-3	±0.2
3-6	±0.3
6-30	±0.5
30-120	±0.8
120-400	±1.2
400-1000	±2

1

2

3

4

5

6