


减速比 (Ratio i)		3	4	5	6	8	10	3-6	±0.3
额定承载扭矩(Rated load torque)	Nm	400	800	700	550	450	210	6-30	±0.5
最大加速力矩 (Max.acceleration torque)	Nm	720	1440	1260	990	810	378	30-120	±0.8
急停扭矩 (Emergency stop toque)	Nm	1200	2400	2100	1650	1350	630	120-400	±1.2
								400-1000	±2
精密行星减速机技术参数								精密行星减速机 Precision Planetary Gear Boxes	
容许最大径向载荷 (Max.radial load)	3600N	空载力矩20℃(No-load torque)			≤ 0.72Nm				PS142L1-i-P2-S2 35-79-114.3-200-M12
容许最大轴向载荷 (Max.axial load)	8000N	润滑(Lubrication)			合成润滑脂 (Synthetic grease)				
额定输入转速 (Nominal input speed)	2000r/min	使用环境温度(Operation temperature)			-15℃~+90℃				
最大输入转速 (Max input speed)	4000r/min	使用寿命(Service life)			≥20000h			A. PS.	142.
噪音 (Noise)	≤ 52db	防护等级(Protection grade)			IP54				
回程间隙 (Backlash)	8arcmin	PS 系列			Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn				
		P2 L1							