

1

2

3

4

5

6


A

B



C

D

输出端
OutPut



输入端
InPut



A

B

C

D

减速比 (Ratio i)		9	12/16/20/32	15/40/25/50/30	64/80			6-30	±0.5
额定承载扭矩(Rated load torque)		Nm	400	800	700	450		30-120	±0.8
最大加速力矩 (Max.acceleration torque)		Nm	720	1440	1260	810		120-400	±1.2
急停扭矩 (Emergency stop torque)		Nm	1200	2400	2100	1350		400-1000	±2
精密行星减速机技术参数								精密行星减速机	
								Precision Planetary Gear Boxes	
容许最大径向载荷 (Max.radial load)		3600N	空载力矩20℃(No-load torque)			≤ 0.72Nm			
容许最大轴向载荷 (Max.axial load)		8000N	润滑(Lubrication)			合成润滑油 (Synthetic grease)			
额定输入转速 (Nominal input speed)		2000r/min	使用环境温度(Operation temperature)			-15℃~+90℃			
最大输入转速 (Max input speed)		4000r/min	使用寿命(Service life)			≥20000h			
噪音 (Noise)		≤ 52db	防护等级(Protection grade)			IP54			
回程间隙 (Backlash)		10arcmin			PS系列	Tel/电话: 0533-6288333 6288444		A. PS.	142.
					P2 L2	Fax/传真: 0533-6288411 Web/网址: www.newstart.cn			

未注线性尺寸极限偏差 Unmarked tolerance	
0.5-3	±0.2
3-6	±0.3
6-30	±0.5
30-120	±0.8
120-400	±1.2
400-1000	±2

1

2

3

4

5

6