

1

2

3

4

5

6


A

B



C

D

输出端
OutPut



输入端
InPut




A

B

C

D

减速比 (Ratio i)		9		12/16/20/32		15/40/25/50/30		64/80					6-30	±0.5
额定承载扭矩(Rated load torque)		Nm	400	800		700		450					30-120	±0.8
最大加速力矩 (Max.acceleration torque)		Nm	720	1440		1260		810					120-400	±1.2
急停扭矩 (Emergency stop toque)		Nm	1200	2400		2100		1350					400-1000	±2
精密行星减速机技术参数												精密行星减速机		
容许最大径向载荷 (Max.radial load)		3600N	空载力矩20℃(No-load torque)				≤ 0.72Nm				Precision Planetary Gear Boxes			
容许最大轴向载荷 (Max.axial load)		8000N	润滑(Lubrication)				合成润滑油 (Synthetic grease)							
额定输入转速 (Nominal input speed)		2000r/min	使用环境温度(Operation temperature)				-15℃~+90℃							
最大输入转速 (Max input speed)		4000r/min	使用寿命(Service life)				≥20000h				PS142L2-i-P2-S2 24-58-110-145-M8			
噪音 (Noise)		≤ 52db	防护等级(Protection grade)				IP54							
回程间隙 (Backlash)		10arcmin				PS 系列		Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn				A. PS. 142.		
						P2 L2								

未注线性尺寸极限偏差 Unmarked tolerance	
0.5-3	±0.2
3-6	±0.3
6-30	±0.5
30-120	±0.8
120-400	±1.2
400-1000	±2

1

2

3

4

5

6