

A

B

C

D

1

2


3

4



5

6

输出端  
OutPut



输入端  
InPut




减速比 (Ratio i)	9	12/16/20/32	15/40/25/50/30	64/80			
额定承载扭矩 (Rated load torque) Nm	400	800	700	450			
最大加速力矩 (Max.acceleration torque) Nm	720	1440	1260	810			
急停扭矩 (Emergency stop torque) Nm	1200	2400	2100	1350			

未注线性尺寸极限偏差 Unmarked tolerance	
0.5-3	±0.2
3-6	±0.3
6-30	±0.5
30-120	±0.8
120-400	±1.2
400-1000	±2

精密行星减速机技术参数			
容许最大径向载荷 (Max.radial load)	3600N	空载力矩20℃(No-load torque)	≤ 0.72Nm
容许最大轴向载荷 (Max.axial load)	8000N	润滑(Lubrication)	合成润滑油 (Synthetic grease)
额定输入转速 (Nominal input speed)	2000r/min	使用环境温度 (Operation temperature)	-15℃~+90℃
最大输入转速 (Max input speed)	4000r/min	使用寿命 (Service life)	≥20000h
噪音 (Noise)	≤ 52db	防护等级 (Protection grade)	IP54
回程间隙 (Backlash)	10arcmin	PS系列	Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn
		P2 L2	

精密行星减速机  
Precision Planetary  
Gear Boxes

  
纽氏達特

PS142L2-i-P2-S2  
35-79-114.3-200-M12

A. PS. 142.

1

2

3

4

5

6

A

B

C

D