

1

2

3

4

5

6



A

B


C

D

输出端  
OutPut



输入端  
InPut



A

B

C

D

减速比 (Ratio i)		3	4	5	6	8	10		3-6	±0.3
额定承载扭矩(Rated load torque)		Nm	400	800	700	550	450	210	6-30	±0.5
最大加速力矩 (Max.acceleration torque)		Nm	720	1440	1260	990	810	378	30-120	±0.8
急停扭矩 (Emergency stop toque)		Nm	1200	2400	2100	1650	1350	630	120-400	±1.2
									400-1000	±2
精密行星减速机技术参数									精密行星减速机	
容许最大径向载荷 (Max.radial load)		3600N	空载力矩20℃(No-load torque)				≤ 0.72Nm		Precision Planetary Gear Boxes	
容许最大轴向载荷 (Max.axial load)		8000N	润滑(Lubrication)				合成润滑油脂 (Synthetic grease)			
额定输入转速 (Nominal input speed)		2000r/min	使用环境温度(Operation temperature)				-15℃~+90℃		PS142L1-i-P2-S2	
最大输入转速 (Max input speed)		4000r/min	使用寿命(Service life)				≥20000h		38-80-180-215-M12	
噪音 (Noise)		≤ 52db	防护等级(Protection grade)				IP54		A. PS. 142.	
回程间隙 (Backlash)		8arcmin			PS系列		Tel/电话: 0533-6288333 6288444			
					P2 L1		Fax/传真: 0533-6288411			
							Web/网址: www.newstart.cn			

1

2

3

4

5

6