


减速比 (Ratio i)		9	12/16/20/32	15/40/25/50/30	64/80			6-30	±0.5
额定承载扭矩 (Rated load torque)	Nm	743	1780	1153	800			30-120	±0.8
最大加速力矩 (Max. acceleration torque)	Nm	1337	3204	2075.4	1440			120-400	±1.2
急停扭矩 (Emergency stop torque)	Nm	2229	5340	3459	2400			400-1000	±2
精密行星减速机技术参数								精密行星减速机	
								Precision Planetary Gear Boxes	
容许最大径向载荷 (Max. radial load)	18000N	空载力矩20℃ (No-load torque)			≤ 1.5Nm			 纽氏达特	
容许最大轴向载荷 (Max. axial load)	28000N	润滑 (Lubrication)			合成润滑油 (Synthetic grease)				
额定输入转速 (Nominal input speed)	1500r/min	使用环境温度 (Operation temperature)			-15℃ +90℃			PS190L2-i-P2-S2 35-79-114.3-200-M12	
最大输入转速 (Max input speed)	3000r/min	使用寿命 (Service life)			≥20000h				
噪音 (Noise)	≤ 72db	防护等级 (Protection grade)			IP54				
回程间隙 (Backlash)	10arcmin			PS系列	Tel/电话: 0533-6288333 6288444			A. PS. 190.	
				P2 L2	Fax/传真: 0533-6288411				
				Web/网址: www.newstart.cn					