


減速比 (Ratio i)		60	64	80	100	120	160	200	256	320	512
額定承载扭矩 (Rated load torque)	Nm	3912	3912	3912	3912	3912	3912	2640	3912	2640	1490
最大加速力矩 (Max. acceleration torque)	Nm	7042	7042	7042	7042	7042	7042	4752	7041.6	4752	2682
急停扭矩 (Emergency stop torque)	Nm	11736	11736	11736	11736	11736	11736	7920	11736	7920	4470

未注线性尺寸极限偏差 Unmarked tolerance	
0.5-3	$\pm 0.2$
3-6	$\pm 0.3$
6-30	$\pm 0.5$
30-120	$\pm 0.8$
120-400	$\pm 1.2$
400-1000	$\pm 2$

精密行星减速机技术参数					精密行星减速机 Precision Planetary Gear Boxes	
容许最大径向载荷 (Max. radial load)	35000N	空载力矩20℃ (No-load torque)		≤ 3Nm		
容许最大轴向载荷 (Max. axial load)	32000N	润滑 (Lubrication)		合成润滑脂 (Synthetic grease)		
额定输入转速 (Nominal input speed)	2000r/min	使用环境温度 (operation temperature)		-15℃~+90℃		
最大输入转速 (Max input speed)	4000r/min	使用寿命 (Service life)		≥20000h		
噪音 (Noise)	≤ 75db	防护等级 (Protection grade)		IP54		
回程间隙 (Backlash)	20arcmin		PS 系列	Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn		
			P2 L3			



紐氏達特

PS240L3-i-P2-S2  
42-116-200-235-M12

A. PS. 240.