


减速比 (Ratio i)		3	4	5	6	8	10
额定承载扭矩 (Rated load torque)	Nm	4358	6998	4557	3247	2133	832
最大加速力矩 (Max. acceleration torque)	Nm	7844	12596	8203	5845	3839	1498
急停扭矩 (Emergency stop toque)	Nm	13074	20994	13671	9741	6399	2496

未注线性尺寸极限偏差 Unmarked tolerance	
0.5-3	± 0.2
3-6	± 0.3
6-30	± 0.5
30-120	± 0.8
120-400	± 1.2
400-1000	± 2

精密行星减速机技术参数					精密行星减速机 Precision Planetary Gear Boxes	
容许最大径向载荷 (Max.radial load)	45000N	空载力矩20℃ (No-load torque)		≤ 3Nm		
容许最大轴向载荷 (Max.axial load)	53000N	润滑 (Lubrication)		合成润滑油 (Synthetic grease)		
额定输入转速 (Nominal input speed)	1000r/min	使用环境温度 (Operation temperature)		-15℃~+90℃		
最大输入转速 (Max input speed)	2000r/min	使用寿命 (Service life)		≥20000h		
噪音 (Noise)	≤ 75db	防护等级 (Protection grade)		IP54		
回程间隙 (Backlash)	16arcmin		PS系列	Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn		
			P2 L1			
				 PS285L1-i-P2-S2 55-110-250-300-M16 A. PS. 285.		