


减速比 (Ratio i)		60/64/80/160/256	100/120/200/320	512	6-30	±0.5
额定承载扭矩 (Rated load torque)		Nm 45	41	18	30-120	±0.8
最大加速力矩 (Max. acceleration torque)		Nm 81	73.8	32.4	120-400	±1.2
急停扭矩 (Emergency stop torque)		Nm 135	123	54	400-1000	±2
精密行星减速机技术参数					精密行星减速机	
容许最大径向载荷 (Max. radial load)		480N	空载力矩20℃ (No-load torque)	≤ 0.1Nm	Precision Planetary Gear Boxes	
容许最大轴向载荷 (Max. axial load)		600N	润滑 (Lubrication)	合成润滑脂 (Synthetic grease)		
额定输入转速 (Nominal input speed)		3000r/min	使用环境温度 (Operation temperature)	-15℃~+90℃	PS070L3-i-P2-S2 14-30-50-70-M5	
最大输入转速 (Max input speed)		6000r/min	使用寿命 (Service life)	≥20000h		
噪音 (Noise)		≤ 60db	防护等级 (Protection grade)	IP54		
回程间隙 (Backlash)		12arcmin	PS 系列	Tel/电话: 0533-6288333 6288444	A. PS. 070.	
			P2 L3	Fax/传真: 0533-6288411 Web/网址: www.newstart.cn		