


减速比 (Ratio i)		9	12/16/20/32	15/40/25/50/30	64/80					6-30	±0.5	
额定承载扭矩(Rated load torque)		Nm	22	45	41	18				30-120	±0.8	
最大加速力矩 (Max.acceleration torque)		Nm	39.6	81	73.8	32.4				120-400	±1.2	
急停扭矩 (Emergency stop toque)		Nm	66	135	123	54				400-1000	±2	
精密行星减速机技术参数										精密行星减速机		
容许最大径向载荷 (Max.radial load)		480N	空载力矩20℃(No-load torque)			≤ 0.1Nm				Precision Planetary Gear Boxes		
容许最大轴向载荷 (Max.axial load)		600N	润滑(Lubrication)			合成润滑油 (Synthetic grease)						
额定输入转速 (Nominal input speed)		3000r/min	使用环境温度(Operation temperature)			-15℃~+90℃				紐氏達特		
最大输入转速 (Max input speed)		6000r/min	使用寿命(Service life)			≥20000h				PS070L2-i-P2-S2		
噪音 (Noise)		≤ 60db	防护等级(Protection grade)			IP54				14-30-50-70-M5		
回程间隙 (Backlash)		10arcmin			PS系列		Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn				A. PS. 070.	
					P2 L2							