


| | | | | | | | |
|----------------------------------|--|------------------|-------------------------------|-------|---|---|---|
| 减速比 (Ratio i) | | 60/64/80/160/256 | 100/120/200/320 | 512 | 6-30 | ±0.5 | |
| 额定承载扭矩(Rated load torque) | | Nm | 45 | 41 | 18 | 30-120 | ±0.8 |
| 最大加速力矩 (Max.acceleration torque) | | Nm | 81 | 73.8 | 32.4 | 120-400 | ±1.2 |
| 急停扭矩 (Emergency stop toque) | | Nm | 135 | 123 | 54 | 400-1000 | ±2 |
| 精密行星减速机技术参数 | | | | | | 精密行星减速机 Precision Planetary Gear Boxes | |
| 容许最大径向载荷 (Max.radial load) | | 480N | 空载力矩20℃(No-load torque) | | ≤ 0.1Nm | |  |
| 容许最大轴向载荷 (Max.axial load) | | 600N | 润滑(Lubrication) | | 合成润滑脂 (Synthetic grease) | | |
| 额定输入转速 (Nominal input speed) | | 3000r/min | 使用环境温度(Operation temperature) | | -15℃~+90℃ | | PS070L3-i-P2-S2 8-25-30-46-M4 |
| 最大输入转速 (Max input speed) | | 6000r/min | 使用寿命(Service life) | | ≥20000h | | |
| 噪音 (Noise) | | ≤ 60db | 防护等级(Protection grade) | | IP54 | | |
| 回程间隙 (Backlash) | | 12arcmin | | PS 系列 | Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn | | A. PS. 070. |
| | | | | P2 L3 | | | |