


减速比 (Ratio i)		9	12/16/20/32	15/40/25/50/30	64/80				6-30	±0.5
额定承载扭矩 (Rated load torque)	Nm	40	110	90	50				30-120	±0.8
最大加速力矩 (Max. acceleration torque)	Nm	72	198	162	90				120-400	±1.2
急停扭矩 (Emergency stop torque)	Nm	120	330	270	150				400-1000	±2
精密行星减速机技术参数									精密行星减速机	
									Precision Planetary Gear Boxes	
容许最大径向载荷 (Max. radial load)	900N	空载力矩20℃ (No-load torque)			≤ 0.2Nm				 NEWSTART® 纽氏達特	
容许最大轴向载荷 (Max. axial load)	1200N	润滑 (Lubrication)			合成润滑油 (Synthetic grease)					
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)			-15℃~+90℃					
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)			≥20000h					
噪音 (Noise)	≤ 60db	防护等级 (Protection grade)			IP54					
回程间隙 (Backlash)	10arcmin	PS系列			Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn				PS090L2-i-P2-S2 14-30-50-70-M5	
		P2 L2							A. PS. 090.	