



减速比 (Ratio i)		3	4	5	6	8	10		3-6	±0.3
额定承载扭矩(Rated load torque)	Nm	40	110	90	55	50	32		6-30	±0.5
最大加速力矩 (Max.acceleration torque)	Nm	72	198	162	99	90	57.6		30-120	±0.8
急停扭矩 (Emergency stop toque)	Nm	120	330	270	165	150	96		120-400	±1.2
									400-1000	±2
精密行星减速机技术参数									精密行星减速机 Precision Planetary Gear Boxes	
容许最大径向载荷 (Max.radial load)	900N	空载力矩20℃ (No-load torque)			≤ 0.2Nm					PS090L1-i-P2-S2 22-58-110-145-M8
容许最大轴向载荷 (Max.axial load)	1200N	润滑 (Lubrication)			合成润滑脂 (Synthetic grease)					
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)			-15℃~+90℃					
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)			≥20000h					A. PS. 090.
噪音 (Noise)	≤ 60db	防护等级 (Protection grade)			IP54					
回程间隙 (Backlash)	8arcmin									
					Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn					