


减速比 (Ratio i)		9	12/16/20/32	15/40/25/50/30	64/80				6-30	±0.5		
额定承载扭矩(Rated load torque)	Nm	40	110	90	50				30-120	±0.8		
最大加速力矩 (Max.acceleration torque)	Nm	72	198	162	90				120-400	±1.2		
急停扭矩 (Emergency stop torque)	Nm	120	330	270	150				400-1000	±2		
精密行星减速机技术参数									精密行星减速机			
									Precision Planetary Gear Boxes			
容许最大径向载荷 (Max.radial load)	900N	空载力矩20℃(No-load torque)			≤ 0.2Nm							
容许最大轴向载荷 (Max.axial load)	1200N	润滑油(Lubrication)			合成润滑脂 (Synthetic grease)							
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度(Operation temperature)			-15℃~+90℃				PS090L2-i-P2-S2 19-40-70-90-M5			
最大输入转速 (Max input speed)	6000r/min	使用寿命(Service life)			≥20000h							
噪音 (Noise)	≤ 60db	防护等级(Protection grade)			IP54				A. PS. 090.			
回程间隙 (Backlash)	10arcmin	PS 系列			Tel/电话: 0533-6288333 6288444							
					P2 L2				Fax/传真: 0533-6288411			
									Web/网址: www.newstart.cn			