



减速比 (Ratio i)		1	2						3-6	±0.3
额定承载扭矩 (Rated load torque)	Nm	150	150						6-30	±0.5
最大加速力矩 (Max. acceleration torque)	Nm	225	225						30-120	±0.8
									120-400	±1.2
急停扭矩 (Emergency stop torque)	Nm	450	450						400-1000	±2
精密行星减速机技术参数									精密行星减速机	
容许最大径向载荷 (Max. radial load)	2100N	空载力矩 20℃ (No-load torque)			≤ 0.36Nm				Precision Planetary Gear Boxes	
容许最大轴向载荷 (Max. axial load)	1050N	润滑 (Lubrication)			合成润滑油 (Synthetic grease)					
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)			-15℃~+90℃				PW110L1-i-S2-24-58-110-145-M8	
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)			≥20000h				A. PW. 110.	
噪音 (Noise)	≤ 68db	防护等级 (Protection grade)			IP54					
回程间隙 (Backlash)	6arcmin	PW系列			Tel/电话: 0533-6288333 6288444					
		P2 L1			Fax/传真: 0533-6288411					
					Web/网址: www.newstart.cn					