


减速比 (Ratio i)		60	64	80	100	120	125	150	160	200	6-30	±0.5
额定承载扭矩(Rated load torque)		Nm		150							30-120	±0.8
最大加速力矩 (Max.acceleration torque)		Nm		225							120-400	±1.2
急停扭矩 (Emergency stop toque)		Nm		450							400-1000	±2
精密行星减速机技术参数											精密行星减速机	
容许最大径向载荷 (Max.radial load)		2100N	空载力矩20℃(No-load torque)				≤ 0.36Nm				Precision Planetary Gear Boxes	
容许最大轴向载荷 (Max.axial load)		1050N	润滑(Lubrication)				合成润滑油脂 (Synthetic grease)					
额定输入转速 (Nominal input speed)		3000r/min	使用环境温度(Operation temperature)				-15℃+90℃				NEWSTART® 纽氏達特	
最大输入转速 (Max input speed)		6000r/min	使用寿命(Service life)				≥20000h				PW110L3-i-S2-19-40-70-90-M6	
噪音 (Noise)		≤ 68db	防护等级(Protection grade)				IP54				A. PW. 110.	
回程间隙 (Backlash)		12arcmin			PW系列		Tel/电话: 0533-6288333 6288444					
					P2 L3		Fax/传真: 0533-6288411					
							Web/网址: www.newstart.cn					