


| | | | | | | | | | | | | |
|-----------------------------------|-----------|--------------------------------|----|----|-------|--------------------------|---|----|----|----|---|------|
| 减速比 (Ratio i) | | 12 | 15 | 16 | 20 | 25 | 30 | 32 | 40 | 50 | 6-30 | ±0.5 |
| 额定承载扭矩 (Rated load torque) | Nm | 150 | | | | | | | | | 30-120 | ±0.8 |
| 最大加速力矩 (Max. acceleration torque) | Nm | 225 | | | | | | | | | 120-400 | ±1.2 |
| 急停扭矩 (Emergency stop torque) | Nm | 450 | | | | | | | | | 400-1000 | ±2 |
| 精密行星减速机技术参数 | | | | | | | | | | | 精密行星减速机 Precision Planetary Gear Boxes | |
| 容许最大径向载荷 (Max. radial load) | 2100N | 空载力矩20℃ (No-load torque) | | | | ≤ 0.36Nm | | | | |  | |
| 容许最大轴向载荷 (Max. axial load) | 1050N | 润滑 (Lubrication) | | | | 合成润滑脂 (Synthetic grease) | | | | | | |
| 额定输入转速 (Nominal input speed) | 3000r/min | 使用环境温度 (Operation temperature) | | | | -15℃~+90℃ | | | | | PW110L2-i-K2-19-40- 70-90-M6 | |
| 最大输入转速 (Max input speed) | 6000r/min | 使用寿命 (Service life) | | | | ≥20000h | | | | | | |
| 噪音 (Noise) | ≤ 68db | 防护等级 (Protection grade) | | | | IP54 | | | | | | |
| 回程间隙 (Backlash) | 10arcmin | | | | PW系列 | | Tel/电话: 0533-6288333 6288444 | | | | A. PW. 110. | |
| | | | | | P2 L2 | | Fax/传真: 0533-6288411 Web/网址: www.newstart.cn | | | | | |