


减速比 (Ratio i)		3	4	5	6	8	10		3-6	±0.3
额定承载扭矩(Rated load torque)		Nm	150	150	150	150	150	150	6-30	±0.5
最大加速力矩 (Max.acceleration torque)		Nm	225	225	225	225	225	225	30-120	±0.8
急停扭矩 (Emergency stop toque)		Nm	450	450	450	450	450	450	120-400	±1.2
									400-1000	±2
精密行星减速机技术参数									精密行星减速机	
									Precision Planetary Gear Boxes	
容许最大径向载荷 (Max.radial load)		2100N	空载力矩20℃(No-load torque)			≤ 0.36Nm				紐氏達特
容许最大轴向载荷 (Max.axial load)		1050N	润滑(Lubrication)			合成润滑脂 (Synthetic grease)				
额定输入转速 (Nominal input speed)		3000r/min	使用环境温度(Operation temperature)			-15℃+90℃				
最大输入转速 (Max input speed)		6000r/min	使用寿命(Service life)			≥20000h				
噪音 (Noise)		≤ 68db	防护等级(Protection grade)			IP54			PW110L1-i-24-58-110-145-M8	
回程间隙 (Backlash)		8arcmin				PW系列			A. PW.	110.
						P2 L1				
Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn										

未注线性尺寸极限偏差 Unmarked tolerance	
0.5-3	± 0.2
3-6	± 0.3
6-30	± 0.5
30-120	± 0.8
120-400	± 1.2
400-1000	± 2