



减速比 (Ratio i)	1	2						
额定承载扭矩 (Rated load torque) Nm	150	150						
最大加速力矩 (Max. acceleration torque) Nm	225	225						
急停扭矩 (Emergency stop torque) Nm	450	450						
精密行星减速机技术参数								
容许最大径向载荷 (Max. radial load)	2100N	空载力矩20℃ (No-load torque)	$\leq 0.36Nm$					
容许最大轴向载荷 (Max. axial load)	1050N	润滑 (Lubrication)	合成润滑油 (Synthetic grease)					
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)	$-15^{\circ}C \sim +90^{\circ}C$					
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)	$\geq 20000h$					
噪音 (Noise)	$\leq 68db$	防护等级 (Protection grade)	IP54					
回程间隙 (Backlash)	6arcmin		PW系列					
			P2 L1					
Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn								

未注线性尺寸极限偏差 Unmarked tolerance	
0.5-3	$\pm 0.2$
3-6	$\pm 0.3$
6-30	$\pm 0.5$
30-120	$\pm 0.8$
120-400	$\pm 1.2$
400-1000	$\pm 2$
精密行星减速机 Precision Planetary Gear Boxes	
 纽氏達特	
PW110L1-i-S2-19-55- 95-115-M8	
A. PW.	110.