


减速比 (Ratio i)		12	15	16	20	25	30	32	40	50	6-30	±0.5	
额定承载扭矩 (Rated load torque) Nm		150									30-120	±0.8	
最大加速力矩 (Max.acceleration torque) Nm		225									120-400	±1.2	
急停扭矩 (Emergency stop torque) Nm		450									400-1000	±2	
精密行星减速机技术参数											精密行星减速机 Precision Planetary Gear Boxes		
容许最大径向载荷 (Max.radial load)		2100N	空载力矩20℃ (No-load torque)				≤ 0.36Nm				 紐氏達特		
容许最大轴向载荷 (Max.axial load)		1050N	润滑 (Lubrication)				合成润滑油 (Synthetic grease)						
额定输入转速 (Nominal input speed)		3000r/min	使用环境温度 (operation temperature)				-15℃~+90℃						
最大输入转速 (Max input speed)		6000r/min	使用寿命 (Service life)				≥20000h						
噪音 (Noise) ≤		68db	防护等级 (Protection grade)				IP54				PW110L2-i-K2-OP1		
回程间隙 (Backlash)		10arcmin				PW系列		Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn				A. PW. 110.	
					P2 L2								