


减速比 (Ratio i)		1	2						3-6	±0.3
额定承载扭矩 (Rated load torque)		Nm	360	330					6-30	±0.5
最大加速力矩 (Max.acceleration torque)		Nm	540	495					30-120	±0.8
急停扭矩 (Emergency stop toque)		Nm	1080	990					120-400	±1.2
									400-1000	±2
精密行星减速机技术参数									精密行星减速机	
容许最大径向载荷 (Max. radial load)		2700N	空载力矩20℃ (No-load torque)			≤ 0.36Nm			Precision Planetary Gear Boxes	
容许最大轴向载荷 (Max. axial load)		1350N	润滑 (Lubrication)			合成润滑油 (Synthetic grease)			 NEWSTART® 纽氏達特	
额定输入转速 (Nominal input speed)		2000r/min	使用环境温度 (Operation temperature)			-15℃ +90℃			PW140L1-i-K2-0P1	
最大输入转速 (Max input speed)		4000r/min	使用寿命 (Service life)			≥20000h				
噪音 (Noise)		≤ 70db	防护等级 (Protection grade)			IP54				
回程间隙 (Backlash)		6arcmin			PW 系列	Tel/电话: 0533-6288333 6288444			A. PW. 140.	
					P2 L1	Fax/传真: 0533-6288411				
						Web/网址: www.newstart.cn				