


减速比 (Ratio i)		12	15	16	20	25	30	32	40	50	6-30	±0.5
额定承载扭矩(Rated load torque)	Nm	360									30-120	±0.8
最大加速力矩 (Max.acceleration torque)	Nm	540									120-400	±1.2
急停扭矩 (Emergency stop torque)	Nm	1080									400-1000	±2
精密行星减速机技术参数											精密行星减速机	
容许最大径向载荷 (Max.radial load)	2700N	空载力矩20℃(No-load torque)					≤ 0.36Nm				Precision Planetary Gear Boxes	
容许最大轴向载荷 (Max.axial load)	1350N	润滑(Lubrication)					合成润滑油 (Synthetic grease)					
额定输入转速 (Nominal input speed)	2000r/min	使用环境温度(Operation temperature)					-15℃+90℃					
最大输入转速 (Max input speed)	4000r/min	使用寿命(Service life)					≥20000h				PW140L2-i-S2-19-40-70-90-M6	
噪音 (Noise)	≤ 70db	防护等级(Protection grade)					IP54				A. PW. 140.	
回程间隙 (Backlash)	10arcmin				PW系列		Tel/电话: 0533-6288333 6288444					
					P2 L2		Fax/传真: 0533-6288411 Web/网址: www.newstar.cn					