


减速比 (Ratio i)		60	64	80	100	120	125	150	160	200	6-30	±0.5	
额定承载扭矩 (Rated load torque)	Nm	360									30-120	±0.8	
最大加速力矩 (Max. acceleration torque)	Nm	540									120-400	±1.2	
急停扭矩 (Emergency stop torque)	Nm	1080									400-1000	±2	
精密行星减速机技术参数											精密行星减速机		
											Precision Planetary Gear Boxes		
容许最大径向载荷 (Max. radial load)	2700N	空载力矩 20℃ (No-load torque)				≤ 0.36Nm					 <b>NEWSTART®</b> 纽氏德特		
容许最大轴向载荷 (Max. axial load)	1350N	润滑 (Lubrication)				合成润滑脂 (Synthetic grease)							
额定输入转速 (Nominal input speed)	2000r/min	使用环境温度 (Operation temperature)				-15℃~+90℃							
最大输入转速 (Max input speed)	4000r/min	使用寿命 (Service life)				≥20000h							
噪音 (Noise)	≤ 70db	防护等级 (Protection grade)				IP54					PW140L3-i-K2-19-55-95-115-M8		
回程间隙 (Backlash)	12arcmin				PW系列		Tel/电话: 0533-6288333 6288444 Fax/传真: 0533-6288411 Web/网址: www.newstart.cn				A. PW. 140.		
					P2 L3								