


减速比 (Ratio i)		1	2						3-6	±0.3
额定承载扭矩(Rated load torque)	Nm	360	330						6-30	±0.5
最大加速力矩 (Max.acceleration torque)	Nm	540	495						30-120	±0.8
急停扭矩 (Emergency stop toque)	Nm	1080	990						120-400	±1.2
									400-1000	±2
精密行星减速机技术参数									精密行星减速机 Precision Planetary Gear Boxes	
容许最大径向载荷 (Max.radial load)	2700N	空载力矩20℃(No-load torque)				≤ 0.36Nm			 纽氏达特	PW140L1-i-S2-24-58-110-145-M8
容许最大轴向载荷 (Max.axial load)	1350N	润滑(Lubrication)				合成润滑脂 (Synthetic grease)				
额定输入转速 (Nominal input speed)	2000r/min	使用环境温度(Operation temperature)				-15℃~+90℃				
最大输入转速 (Max input speed)	4000r/min	使用寿命(Service life)				≥20000h				
噪音 (Noise)	≤ 70db	防护等级(Protection grade)				IP54				
回程间隙 (Backlash)	6arcmin	PW系列				Tel/电话: 0533-6288333 6288444			A. PW.	140.
		P2 L1				Fax/传真: 0533-6288411 Web/网址: www.newstart.cn				