


减速比 (Ratio i)		60	64	80	100	120	125	150	160	200	6-30	±0.5
额定承载扭矩 (Rated load torque)	Nm	585									30-120	±0.8
最大加速力矩 (Max. acceleration torque)	Nm	878									120-400	±1.2
急停扭矩 (Emergency stop torque)	Nm	1755									400-1000	±2
精密行星减速机技术参数											精密行星减速机	
容许最大径向载荷 (Max. radial load)	3800N	空载力矩20℃ (No-load torque)					≤ 0.72Nm				Precision Planetary Gear Boxes	
容许最大轴向载荷 (Max. axial load)	1900N	润滑 (Lubrication)					合成润滑脂 (Synthetic grease)				 紐氏達特	
额定输入转速 (Nominal input speed)	1500r/min	使用环境温度 (Operation temperature)					-15℃~+90℃					
最大输入转速 (Max input speed)	3000r/min	使用寿命 (Service life)					≥20000h				PW170L3-i-S2-19-40-90-M6	
噪音 (Noise)	≤ 72db	防护等级 (Protection grade)					IP54				A. PW. 170.	
回程间隙 (Backlash)	12arcmin				PW系列		Tel/电话: 0533-6288333 6288444					
					P2 L3		Fax/传真: 0533-6288411 Web/网址: www.newstart.cn					