

1

2

3

4

5





6

A

B

C

D




A

B

C

D

减速比 (Ratio i)		1	2							3-6	±0.3
额定承载扭矩(Rated load torque)		Nm	585	544						6-30	±0.5
最大加速力矩 (Max.acceleration torque)		Nm	878	816						30-120	±0.8
急停扭矩 (Emergency stop toque)		Nm	1755	1632						120-400	±1.2
										400-1000	±2
精密行星减速机技术参数										精密行星减速机	
										Precision Planetary Gear Boxes	
容许最大径向载荷 (Max.radial load)	3800N	空载力矩20℃(No-load torque)				≤ 0.72Nm				 PW170L1-i-K2-35-79-114.3-200-M12	
容许最大轴向载荷 (Max.axial load)	1900N	润滑(Lubrication)				合成润滑脂 (Synthetic grease)					
额定输入转速 (Nominal input speed)	1500r/min	使用环境温度(Operation temperature)				-15℃+90℃					
最大输入转速 (Max input speed)	3000r/min	使用寿命(Service life)				≥20000h					
噪音 (Noise)	≤ 72db	防护等级(Protection grade)				IP54					
回程间隙 (Backlash)	6arcmin			PW 系列		Tel/电话: 0533-6288333 6288444				A. PW. 170.	
				P2 L1		Fax/传真: 0533-6288411 Web/网址: www.newstart.cn					

1

2

3

4

5

6