


减速比 (Ratio i)		12	15	16	20	25	30	32	40	50	6-30	±0.5	
额定承载扭矩 (Rated load torque)		Nm									585	30-120	±0.8
最大加速力矩 (Max.acceleration torque)		Nm									878	120-400	±1.2
急停扭矩 (Emergency stop torque)		Nm									1755	400-1000	±2
精密行星减速机技术参数											精密行星减速机		
容许最大径向载荷 (Max.radial load)		3800N	空载力矩20℃ (No-load torque)				≤ 0.72Nm					Precision Planetary Gear Boxes	
容许最大轴向载荷 (Max.axial load)		1900N	润滑 (Lubrication)				合成润滑油 (Synthetic grease)						
额定输入转速 (Nominal input speed)		1500r/min	使用环境温度 (Operation temperature)				-15℃ +90℃					PW170L2-i-S2-35-79-114.3-200-M12	
最大输入转速 (Max input speed)		3000r/min	使用寿命 (Service life)				≥20000h						
噪音 (Noise)		≤ 72db	防护等级 (Protection grade)				IP54						
回程间隙 (Backlash)		10arcmin	PW系列				Tel/电话: 0533-6288333 6288444						
			P2 L2				Fax/传真: 0533-6288411						
							Web/网址: www.newstart.cn						
											A. PW.	170.	