


减速比 (Ratio i)		1	2					3-6	±0.3
额定承载扭矩 (Rated load torque) Nm		25	24					6-30	±0.5
最大加速力矩 (Max. acceleration torque) Nm		38	36					30-120	±0.8
急停扭矩 (Emergency stop torque) Nm		75	72					120-400	±1.2
								400-1000	±2
精密行星减速机技术参数								精密行星减速机 Precision Planetary Gear Boxes	
容许最大径向载荷 (Max. radial load)	700N	空载力矩20℃ (No-load torque)				≤ 0.1Nm		 纽氏达特	PW65L1-i-K2-14-30-50-70-M5
容许最大轴向载荷 (Max. axial load)	350N	润滑 (Lubrication)				合成润滑脂 (Synthetic grease)			
额定输入转速 (Nominal input speed)	3000r/min	使用环境温度 (Operation temperature)				-15℃~+90℃			
最大输入转速 (Max input speed)	6000r/min	使用寿命 (Service life)				≥20000h		A. PW.	
噪音 (Noise)	≤ 60db	防护等级 (Protection grade)				IP54			
回程间隙 (Backlash)	6arcmin	PW系列				Tel/电话: 0533-6288333 6288444			
		P2 L1				Fax/传真: 0533-6288411			
						Web/网址: www.newstart.cn			